

Serial No. 10/574,172
Atty. Doc. No. 2003P13562WOUS

RECEIVED
CENTRAL FAX CENTER
MAR 02 2009

Amendments To The Claims:

1. - 15. (cancelled)

16. (currently amended) A method for transmitting messages in a network via data terminals connected thereto, comprising:

sending a message to be relayed from a sender data terminal to a first mail processing device assigned to the sender data terminal;

assigning a unique identifier to the message that indicates that a message to be relayed is on the sender data terminal, or in the first mail processing device, wherein the identifier comprises a plurality of subidentifiers, each of which is assigned to at least one message element contained in a relayed message;

sending a test message including the subidentifiers from the first mail processing device to a second mail processing device assigned to a recipient address data terminal;

evaluating in the second mail processing device the test message sent by the first mail processing device, the evaluating configured to process each subidentifier in the test message relative to data present in the second mail processing device indicative of respective message elements previously relayed to the recipient address data terminal;

sending an evaluation-result of the test message from the second mail processing device to the first mail processing device, said evaluation-result of the test message indicating to the first mail processing device to transmit message elements, evaluated as not previously relayed to the recipient address data terminal, to the second mail processing device, and further indicating to block message elements, evaluated as previously relayed to the recipient address data terminal, from being transmitted to the second mail processing device;

transmitting or blocking a transmission of respective ones of the message elements to the second mail processing device in response to the evaluation-result of the test message, wherein said transmitting or blocking of respective ones of the message elements in response to the evaluation-result of the test message is configured to suppress a duplicative reception by the recipient address data terminal of a message element present in a message previously received by the recipient address, and is further configured to ensure that an amended message element of a message element present in the previously received message is transmitted to the recipient address; and

Serial No. 10/574,172

Atty. Doc. No. 2003PI3562WOUS

relaying to the recipient address data terminal respective message elements transmitted from the first mail processing device to the second mail processing device.

17-20. (cancelled)

21. (previously presented) The method according to claim 16, wherein the identifier is evaluated on a mail server in the network.

22. (cancelled)

23. (previously presented) The method according to claim 16, wherein a notification of the blocked transmission is forwarded to the sender and/or recipient if the transmission is blocked on the basis of the evaluation results.

24. (previously presented) The method according to claim 16, wherein the identifier and/or the relevant subidentifier indicates the date and time of creation of the original message where these differ from the time of transmission, and/or an e-mail address of an original sender if this differs from the e-mail address of the sender, and/or the contents of the message or of the respective message element.

25. (previously presented) The method according to claim 16, wherein there is a data terminal for executing the method and having a mail processing device that is designed such that an identifier for the message based on data present concerning the entry of messages at an address data terminal from the past is evaluated in an evaluation unit, and such that, based on the evaluation result, transmission of a message to the address data terminal is triggered or blocked.

26. (previously presented) The method according to claim 25, wherein the mail-processing device forms part of a mail server, which is integrated in the data terminal.

27. (previously presented) The method according to claim 25, wherein a memory unit for storing data concerning the entry of messages at a different data terminal.

Serial No. 10/574,172

Atty. Doc. No. 2003P13562WOUS

28. (currently amended) A network, comprising:

a sending module configured to send a message to be relayed from a sender data terminal to a first mail processing device assigned to the sender data terminal;

an assigning module configured to assign a unique identifier to the message that indicates that a message to be relayed is on the sender data terminal, or in the first mail processing device, wherein the identifier comprises a plurality of subidentifiers, each of which is assigned to at least one message element contained in a relayed message;

a test message sensing module configured to send a test message including the subidentifiers from the first mail processing device to a second mail processing device assigned to a recipient address data terminal;

an evaluator configured to evaluate in the second mail processing device the test message sent by the first mail processing device, the evaluating configured to process each subidentifier in the test message relative to data present in the second mail processing device indicative of respective message elements previously relayed to the recipient address data terminal;

a sending module configured to send an evaluation-result of the test message from the second mail processing device to the first mail processing device, said evaluation-result of the test message indicating to the first mail processing device to transmit message elements, evaluated as not previously relayed to the recipient address data terminal, to the second mail processing device, and further indicating to block message elements, evaluated as previously relayed to the recipient address data terminal, from being transmitted to the second mail processing device;

a module configured to transmit or to block a transmission of respective ones of the message elements to the second mail processing device in response to the evaluation-result message, wherein the transmission or block of respective ones of the message elements in response to the evaluation-result of the test message is configured to suppress a duplicative reception by the recipient address data terminal of a message element present in a message previously received by the recipient address, and is further configured to ensure that an amended message element of the message element present in said previously received message is transmitted to the recipient address; and

a module configured to relay to the recipient address data terminal respective message elements transmitted from the first mail processing device to the second mail processing device.

Serial No. 10/574,172
Atty. Doc. No. 2003P13562WOUS

29. (previously presented) The network according to claim 28, wherein at least one of the mail-processing devices forms part of a mail server.

30. (previously presented) The network according to claim 29, further comprising a memory unit for storing previously relayed message elements.